

Hot and Heavy Collection

DESIGN

Product Type:	Floating LVT
Overall Thickness:	5 mm (.2")
Wear Layer:	20 mil (0.5 mm)
Finish:	M-Force Ultra
Surface Profile:	Wood Emboss; Light Emboss
Edge Profile:	Bevel
Size:	235mm x 1505mm (actual) 9"W x 59"L (nominal)
Square Feet Per Carton:	22.84 sf/ctn (2.12 m ² /ctn)
Pieces Per Carton:	6 pieces/ctn
Pounds Per Carton:	40.78 lbs/ctn (18.49 kg/ctn)
Installation Method:	Loose Lay with Perimeter Glue or Full Spread
Recommended Adhesive:	M95.0 Resilient Flooring Adhesive, M99 Resilient Flooring Adhesive, or M700 Adhesive

SUSTAINABILITY

Certification:	FloorScore® certified
Pre Consumer RC:	37%
Post Consumer RC:	22%

PERFORMANCE

Construction:	Commercial Grade Loose Lay Luxury Vinyl Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM 2421/ASTM F2055 - Passes - ±0.10 in. max
Size And Tolerance:	ASTM 2421/ASTM F2055 - Passes - ±0.016 in. per linear foot
Thickness:	ASTM F386 - Passes - as specified ±0.005 in.
Flexibility:	ASTM F137 - Passes - 1" mandrel
Dimensional Stability:	ASTM F2199 - Passes - 0.020 in. per linear foot
Static Load:	ASTM F970 - Passes, modified - 1000 psi
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%, maximum single read 10%
Resistance To Chemicals:	ASTM F925 - Passes - No Change or Slight Change
Resistance To Light:	ASTM F1515 - Passes - ΔE ≤ 8
Resistance To Heat:	ASTM F1514 - Passes - ΔE ≤ 8
Critical Radiant Flux:	ASTM E648 - Passes - ≥ 0.45 watts/cm ² , Class 1
Smoke Density:	ASTME662 - Part A - less than 450

SERVICE

Warranties:	Limited 20 Year M-Force Ultra Commercial Warranty
-------------	---

